

DONGFENG BRAND TRACTOR SERIES

DF-254G2/304G2/354G2/404G2

25-30 HP (G2 Model)



MODEL DF-254G2 /304G2 4WD

MAIN DISPOSITIONS

Dual-function clutch
Twin turning speeds of PTO

Shuttle shift gear

Synchromesh gear

Power steering
Safe start switch
Fiberglass hood
Combination meter
Quality seat system
Seat belt
Folding ROPS

OPTIONS

Sun shade
Spring seat system
Turf tyre
Industrial tyre
EPA engine
EC engine

35-40 HP (G2 Model)

MAIN DISPOSITIONS

Dual-function clutch
Twin turning speeds of PTO

Shuttle shift gear

Synchromesh gear

Power steering
Safe start switch
Fiberglass hood
Combination meter
Quality seat system
Seat belt
Folding ROPS

OPTIONS

Sun shade
Spring seat system
Turf tyre
Industrial tyre
EPA engine
EC engine



MODEL DF-354G2/404G2 4WD



DONGFENG BRAND TRACTOR SERIES

DF-254G2/304G2/354G2/404G2

Tractor Parameters	Model		DF-254G2	DF-304G2	DF-354G2	DF-404G2
	Drive Type		4WD	4WD	4WD	4WD
	Overall Dimensions L X W X H (mm)		3350X1480X1524	3350X1480X1540	3453X1588X1500	3453X1588X1581
	Wheel Track (mm)	Front	1100	1100	1200	1200
		Rear	1100, 1200, 1300	1100, 1200, 1300	1200, 1300, 1400	1200, 1300, 1400
	Wheel Base (mm)		1732	1732	1900	1900
	Ground Clearancre (mm)	Under front axle	290	310	358	405
	Rated Traction Force (N)	In paddy fields	4200	4950	5160	4970
		In dry fields	6300	6940	7230	7856
	Construction Mass (kg)		1650	1650	1780	1780
	Min. Turning Radius (m)		2.30	2.40	2.50	2.50
Engine Specifications	Model		3LS25B	3LS30B	4LD35B	4LD40B
	Type		Vertical, in-line cylinder arrangement, radiator cooling, 4-stroke cycle			
	Rated Power (kW/hp)		18.4	22.0	25.8	29.4
	Rated Speed (rpm)		2400			
Drive System	Bore X Stroke (mm)		90X95		90X100	
	Total Displacement (L)		1.813		2.543	
	Clutch		Linkage type, double-acting clutch			
	Gearbox		(4+4)X2 Shuttle shift gear and synchromesh gearbox			
	Main Drive		One pair of spiral bevel gears			
	Differential		Bevel gear			
Travelling Mechanism	Differential Lock		Jaw lock			
	Final Transmissions		Spur gear, external gearing			
	Tyre	Front	6.00-16	6.50-16	6.50-16	7.50-16
		Rear	9.50-24	11.2-24	11.2-24	12.4-24
Working Device	Steering Gear		Full hydraulic power steering			
	Brake		Disk type			
	Hydraulic System	Lifting capacity at 610 mm behind lift point (kg)	432	496	580	665
		3-point suspension	Category:I			
	P.T.O.Shaft	Rotating Speed (rpm)	540/1000			
Spline size		6-Ø35 Rectangular spline				

