



中国重汽
SINOTRUK

<https://truckmanualshub.com/>

CANN'S HEAVY EQUIPMENT & MACHINERY

Telephone: (035) 421 – 0697

Email: scann@fullwon.com

Room 301 EBT Building, Rizal Boulevard
Dumaguete City, Negros Oriental 6200



Sinotruk HOWO 371HP 6x4 Concrete Mixer



**Picture is for reference only*

SPECIFICATIONS:

Dimensions	Length (mm): 9040 Width (mm): 2496 Height (mm): 3850 Tank volume: 10cubic Wheel Base (mm): 3825+1350 Front /rear suspension(mm): 1500/2625 Approach/Departure Angle (°): 16/15	Performance	Max. Speed (km/h): 90,102 Max. Speed (km/h)(design): 90,102 Fuel Consumption (L/100km): 35
Weight	Vehicle Curb Weight (kg): 13100 Loading weight(kg): 11770 Gross Comb. Weight (kg): 25000 Gross Comb. Weight (design): 25000		
Engine	Model: WD 615.47 Diesel engine, EURO2 ,6-cylinder in line,4-stroke,water-cooled,turbocharged,air-to-air intercooled Rated Power (HP/r/min): 371HP/273kw, 2200r/min Max. Torque (Nm/r/min): 1350Nm ,1100 ~ 1600r/min Type: Sinotruk ENGINE		
Driving axle	Type: HC16/16ton, double axle/ reduction, Ratio: 4.42/4.8/5.73		
Clutch	Model: Standard B-type (Standard WABCO clutch master cylinder, wheel cylinder) Type: SINOTRUK 430 pull-type diaphragm clutch		
Frame	Transmission Type: HW19710, Max.torque1900Nm,10 gears Type & Advantages: MAN Frame, Enhanced whole front suspension brackets and beams to Improve the reliability of the engine and cab suspension. Large span beams connecting plate and local reinforcement structure make stress distribution more uniform. Stringer standard pitch design in favour of Modular layout and option of the assembly of different wheelbase		
Front Axle	Type: SINOTRUK MADE, HF9, Howo new Style, Standard disc brakes		
Ratio Load(kg)	9000		
FR. Suspension	Type: New SINOTRUK style, spring suspension		
Rear Axle	Type: HC16		
Ratio Load(kg)	16000		
Reduction	Ratio: 4.42/4.8/5.73		
RR. Suspension	Type: New SINOTRUK style, spring suspension		
Steering	Model: ZF8098 Type: ZF steering ,ZF power steering pump, system pressure18Mpa Steering Wheel: Hydraulic steering		
Brake System	Parking: Disc brake		

Driver's Cab

Type: HW70, VOLVO cab

Equipment: Four-point suspension and shock absorber, New style seat, Adjustable steering wheel, European new heaters, Large LCD display, VDO. Instrument and electrical control template, Lateral stability device, Dual-locking structure of seat belt, exterior sun shade

Driver's Seat: Hydraulic shock absorbers

Air-conditioner: with Air Condition

Capacity(L):300L

Type & Size: 12(11) nylon tires

Batteries: 24V

Imported of pumps, motors, reducer

Fuel Tank

Wheel & Tire

Electrical

Mixer