

PRODUCT RECOMMENDATION

TATRA 815 T 815-2 260S25 TERRNO.1 3B-928-10 (1996 AND AFTER)



ENGINE 3B-928-10
Capacity: 30-35 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth NF 10W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 20000 km

DIFFERENTIAL REAR
Capacity: 9 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1071	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 60000 km

HYDRAULIC CLUTCH SYSTEM
Capacity: 0,3 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 36 months

TIPPING GEAR (6x6)
Capacity: 46 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 32	Perlus H 22	Perlus AF 32

Change every 120000 km/ 3 months

TIPPING GEAR (8x8)
Capacity: 120 litre

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 32	Perlus H 22	Perlus AF 32

Change every 120000 km/ 3 months

PRODUCT RECOMMENDATION

TATRA 815 T 815-2 260S25 TERRNO.1 3B-928-10 (1996 AND AFTER)



TRANSFERBOX

Capacity: 10,5 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1071	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 90000 km/ 36 months

TRANSMISSION MANUAL 10TS130 10/2

Capacity: 11 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1071	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 90000 km/ 36 months

TRANSMISSION MANUAL 10TS160 10/2

Capacity: 11 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1071	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 90000 km/ 36 months

TRANSMISSION MANUAL 12TS130 10/2

Capacity: 11 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1071	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 90000 km/ 36 months

TRANSMISSION MANUAL 12TS160 10/2

Capacity: 11 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1071	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 90000 km/ 36 months

PRODUCT RECOMMENDATION

TATRA 815 T 815-2 260S25 TERRNO.1 3B-928-10 (1996 AND AFTER)



HYDRAULIC CAB TILT SYSTEM WITH HYDRAULIC SPARE WHEEL TILT SYSTEM HA 25

Capacity: 1 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 32	Perlus H 22	Perlus AF 32

Change every 120000 km/ 36 months

HYDRAULIC CAB TILT SYSTEM WITH HYDRAULIC SPARE WHEEL TILT SYSTEM Power-Packer

Capacity: 1 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 120000 km/ 36 months

POWER STEERING

Capacity: 4,5 litre

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 32	Perlus H 22	Perlus AF 32

Change every 90000 km/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MP Lithep Grease EP 2		

GREASE POINTS/NIPPLES CLUTCH RELEASE BEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Labora Grease		

Check every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.