



---Language---

[Home](#)[About XCMG](#)[Products](#)[Sales&Services](#)[Contact Us](#)

LW300K

[Home](#) > [Product](#) > [K Series](#)[Product](#)[Series](#)[Selection Survey](#)

Product Quick Access:

[Feature](#)[Parameter](#)[Down load](#)[Back to the list](#)[--Check for other models--](#)

Item	Parameter	Unit
Rated load	3.0	t
Bucket capacity	1.8	m ³
Dumping height	2930	mm
Dumping distance	1000	mm
Max.drawing force	≥120	kN
Max. traction	≥90	kN
Dimension (L×W×H)	7250×2580×3290	mm
Operating weight	10.6	t
Boom lifting time	5.68	s
Total time of three devices	10.3	s
Wheelbase	2900	mm
Min. turning radius (bucket outer)	6067	mm
Rated power	92	kW
Long boom parameter		
Bucket capacity	1.5/1.8	m ³
Rated load	2.7/2.7	t
Dimension (Length × Width × Height)	7540×2580×3290 7640×2580×3290	mm
Dumping height	3290/3225	mm
Dumping distance	1092/1172	mm
Operating weight	10.6/10.8	t
Attachment parameter—grasping grass		
Dumping height	3043	mm
Dumping distance	2036	mm
Clamp body width	2200	mm
Max. opening	2800	mm
Attachment parameter—clamp (III)		
Dumping height	2784	mm
Dumping distance	1134	mm
Min. circle diameter	590	mm

https://truckmanualshub.com/

Max. opening	1700	mm
Attachment parameter—side dumping		
Bucket width	2650	mm
Dimension	7414×2650×3290	mm
Dumping height (straight/side) dumping	2813/3623	mm
Dumping distance (straight/side) dumping	1104/183	mm
Lifting height (straight/side) dumping	5120/6052	mm
Attachment parameter—Sliding fork		
Fork folding angle	20	°
Attachment length	1575	mm
Attachment width	1980	mm
Attachment height	1200	mm
Fork teeth length	1050	mm

> **Online Purchase**



Welcome to purchase XCMG products online, and we will contact you soon.

> **Sales&Services**



Service network spread all over China.

XCMG OA | XCMG Email | Contact XCMG | Satisfaction Survey

Industrial Zone 1, Xuzhou Economic Development Zone, Jiangsu, China



© XCMG Group All Rights Reserved

©2010 XCMG 苏ICP备10206335